

# ITI2000-TXR Transfer Paper Sublimation Printer

## TECHNICAL SPECIFICATIONS

PRINT				
Print head	2, 4 or 6 Ricoh Gen5			
Print modes (sqft/hr)		2 print heads	4 print heads	6 print heads
	605x300 dpi (1 pass)	1,130	2,206	3,336
	605x600 dpi (2 pass)	592	1,130	1,668
	605x900 dpi (3 pass)	376	753	1,130
	605x1200 dpi (4 pass)	269	538	807
Print resolution	Up to 605 x 1200 dpi			
Technology	Piezo-electric inkjet; Greyscale			
Ink type	Dye sublimation			
Ink color	C M Y K; Optional Lc, Lm			
RIP software compatibility	inedit/neoStampa, Caldera 10, Onyx   other drivers available			
File formats	TIFF, JPEG, PS, EPS, PDF			
MEDIA				
Media handling	Vacuum platform; dancer bar tension system			
Media type	Transfer paper			
Media width (max)	78.7"			
Media roll weight (max)	420 lb.			
Media roll diameter (max)	16.5"			
OPERATION				
Standard interface	USB 3.0			
Maximum power	7kw			
Power requirements	220V±5%, single-phase, 50/60 Hz, 32A			
Temperature	68°F to 77°F			
Relative humidity	35% to 65%, non-condensing			
DIMENSIONS & WEIGHT				
Printer dimensions	145.7"L x 55"W x 59"H			
Shipping dimensions	157.5"L x 63"W x 66.9"H			
Weight	2425 lbs. Shipping: 3858 lbs.			
WARRANTY				
One Year Limited Warranty (Please consult your dealer for Warranty details)				

Specifications and terms are subjects to change without notice. ITI is a trademark of Inkjet Technology, Inc. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Copyright 2016 Inkjet Technology, Inc.

ITI2000-TXR 0117 rev 1.2