

ITI3200-TXR Dual Production: Direct-to-Fabric & Transfer Paper Sublimation Printer

TECHNICAL SPECIFICATIONS

PRINT	
Print head	4 to 8 Ricoh Gen 5
Print modes	Production Quality: 1300 sqft/hr (120.7 sqm/hr) 2 pass
	Standard Quality: 970 sqft/hr (90 sqm/hr) 3 pass
	High Quality: 700 sqft/hr (65 sqm/hr) 4 pass
Print resolution	Up to 605 x 1200 dpi
Technology	Piezo-electric inkjet; Greyscale
Ink type	Dye sublimation
Ink color	C M Y K
Ink reservoir size	2.5 liter max. capacity (1 liter ink bottles to refill)
RIP software compatibility	inedit/neoStampa, Caldera 10, Onyx other drivers available
Color management	ICC based color, adjustment curves, density adjustment
File formats	TIFF, JPEG, PS, EPS, PDF
MEDIA	
Media handling	Roll feed
Media types	Polyester fabric, blended fabric, blackout fabric
	Transfer paper from 58 - 140 gsm capability
Media width (max)	128"
Media roll weight (max)	220 lb.
Media roll diameter (max)	16"
Media feeding	Adjustable tension system
Media heaters	In-line dual infrared heaters in front
OPERATION	
Standard interface	USB
Maximum power	Printer: 950 watts Heater/Dryer: 10kw
Power requirements	Printer: 220VAC, single-phase, 50/60 Hz, 16A
	Heater/Dryer: 220VAC, single-phase, 50/60 Hz, 46A
Temperature	68°F to 86°F
Relative humidity	35% to 65%, non-condensing
DIMENSIONS & WEIGHT	
Printer dimensions	205.9"L x 73.5"W x 67.7"H
Shipping dimensions	226"L x 82.7"W x 82.7"H
Weight	2400 lbs.
WARRANTY	
One Year Limited Warranty (Please consult your dealer for Warranty details)	

Specifications and terms are subjects to change without notice. ITI is a trademark of Inkjet Technology, Inc. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Copyright 2016 Inkjet Technology, Inc.

ITI3200-TXR 0117 rev 1.2