

ITI3200-UVR UV-LED Grand Format Printer

TECHNICAL SPECIFICATIONS

PRINT	
Print head	Up to 15 Ricoh print heads
Print modes	Production Quality: 1000 sqft/hr (4 pass)
	Standard Quality: 670 sqft/hr (6 pass)
	High Quality: 490 sqft/hr (8 pass)
Print resolution	Up to 605 x 1200 dpi
Technology	Piezo-electric inkjet; UV-LED
Ink type	UV, pigment-based
Ink color	C M Y K + White (optional)
Ink cartridge size	5 liter
RIP software compatibility	inedit/neoStampa, Caldera 10, Onyx other drivers available
Color management	ICC based color, adjustment curves, density adjustment
File formats	TIFF, JPEG, PS, EPS, PDF
MEDIA	
Media handling	Industrial roll feeding and take-up system
Media types	Vinyl, PET film, blockout, backlit, synthetic paper, banner media
Media width (max)	126"
Media roll weight (max)	800 lb.
Media roll diameter (max)	16"
Media feeding	Dual Servo Motors Feeding System
OPERATION	
Standard interface	USB
UV energy source	Dual UV LED lamps; user selectable power settings
Maximum power	6500 W
Power requirements	220 to 240VAC, single-phase, 50/60 Hz, 30A
Temperature	60°F to 85°F
Relative humidity	20% to 80%, non-condensing
DIMENSIONS & WEIGHT	
Printer dimensions	210"L x 78.3"W x 77.2"H
Weight	7500 lbs.
WARRANTY	
	One Year Limited Warranty (Please consult your dealer for Warranty details)

Specifications and terms are subjects to change without notice. ITI is a trademark of Inkjet Technology, Inc. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Copyright 2016 Inkjet Technology, Inc.

ITI3200-UVR 0117 rev 1.2